



LTF100-V

COMMERCIAL GRADE FLAME RETARDED POLYOLEFIN TUBING

LTF100-V is a commercial grade flexible polyolefin heat shrink tubing designed for applications where cost is an important factor. Common uses include insulation, wire bundling, colour coding, mechanical and chemical protection. A wide range of colours are available from stock and it is flame retarded to UL VW-1.



TECHNICAL DATA

COMMERCIAL GRADE FLAME RETARDED POLYOLEFIN

Material	Polyolefin
Shrink Ratio	2:1
Operating Temperature	-55°C - 125°C
Dielectric Strength	15 KV/mm
Installation Temperature	70°C - 110°C
Specifications	UL 224 VW-1 (E345553) CSA RoHS Compliant

APPLICATIONS

- Insulation and protection of cable harnesses.
- Wire bundling and colour coding.
- Mechanical and chemical protection.

BENEFITS

- Highly flame retardant, UL 224 VW-1 rated material.
- Good chemical and abrasion resistance.
- 2:1 shrink ratio.

Ordering Description	Ordering Size (Inches)	Minimum ID Recovered (mm)	Maximum ID Recovered (mm)	Recovered Wall Thickness (mm)
LTF100V-3/64	3/64	1.20	0.60	0.45
LTF100V-1/16	1/16	1.60	0.80	0.45
LTF100V-3/32	3/32	2.40	1.20	0.50
LTF100V-1/8	1/8	3.20	1.60	0.50
LTF100V-3/16	3/16	4.80	2.40	0.50
LTF100V-1/4	1/4	6.40	3.20	0.65
LTF100V-3/8	3/8	9.50	4.80	0.65
LTF100V-1/2	1/2	12.70	6.40	0.65
LTF100V-3/4	3/4	19.00	9.50	0.75
LTF100V-1	1	25.40	12.70	0.90
LTF100V-1-1/4	1-1/4	31.00	16.00	0.95
LTF100V-1-1/2	1-1/2	38.00	19.00	1.00
LTF100V-2	2	51.00	25.40	1.15
LTF100V-3	3	76.00	38.00	1.25
LTF100V-4	4	102.00	51.00	1.40

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.