

## CT300

### HEAT SHRINKABLE MARKER SLEEVING

CT300 is a printable, 3:1 shrink ratio very flexible polyolefin tubing. It has an ultra thin wall, a large shrink ratio and recovers very rapidly. It is specifically developed for use as part of a marking system. The tubing meets high quality standards and can therefore be used in a wide range of applications including military and professional electronics.



## TECHNICAL DATA

### HEAT SHRINKABLE MARKER SLEEVING

Material	Polyolefin
Shrink Ratio	3:1
Operation Temperature	-55 °C to + 135 °C
Dielectric Strength	20 KV/mm
Installation Temperature	120 °C
Specifications	UL 224 VW1 CSA LR31929 RoHS Compliant

## APPLICATIONS

- Military and professional electronics.
- Designed to be used as part of a marking system.
- Wire and cable identification.

## BENEFITS

- Permanent identification sleeves.
- Computer printable ultra thin wall.
- Excellent print performance, UL224 VW1 flame retardence.
- Good chemical and solvent resistance, 3:1.

Ordering Size (Inches)	Size (mm)	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Minimum Flat Width (mm)	Recovered Wall Width (mm)	Spool Size (m)
3/32	2.4	2.38	0.79	4.8	0.58	100
1/8	3.2	3.20	1.10	5.5	0.58	100
3/16	4.8	4.80	1.60	8.0	0.58	100
1/4	6.4	6.40	2.10	11.0	0.58	100
3/8	9.5	9.50	3.20	16.0	0.61	100
1/2	12.7	12.70	4.20	21.5	0.61	100
3/4	19.1	19.00	6.40	32.0	0.61	100
1	25.4	25.40	8.50	40.0	0.64	100
1-1/2	38.1	38.00	19.00	59.0	0.51	50
2	50.8	50.80	25.40	79.0	0.64	50

## QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.