



HTB-A

ADHESIVE LINED HEAT SHRINK TUBING MINI-SPOOL BOXES

HTB-A's are mini spool boxes containing either 3:1 or 4:1 adhesive lined heat shrinkable tubing. The tubing contained within the boxes is a general purpose, flexible polyolefin tubing with a thermoplastic adhesive liner. The inner liner will melt and flow to environmentally seal and protect components and interconnections.



TECHNICAL DATA

ADHESIVE LINED HEAT SHRINK TUBING MINI-SPOOLS BOXES

Shrink Ratio	3:1 or 4:1
Operating Temperature	-55°C to 110°C
Dielectric Strength	12 KV/mm
Installation Temperature	110°C

APPLICATIONS

- Protection against abrasion and chemicals.
- Wire bundling and splice protection.
- Cable identification and strain relief.
- Sealing and waterproofing of cables.

BENEFITS

- 3:1 shrink ratio allows for connector-to-cable sealing.
- Medium wall provides increased mechanical protection.
- Adhesive bonds to a wide variety of plastics, rubbers and metals including polyethylene, aluminium, steel and copper.

3:1 Ratio Mini Boxes

Ordering Description	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Maximum ID Recovered (mm)	Mini Box Quantity (m)
HTB-A-PLDW100-3/1	3.0	1.0	1.00	5.0
HTB-A-PLDW100-6/2	6.0	2.0	1.10	4.0
HTB-A-PLDW100-9/3	9.0	3.0	1.40	3.0
HTB-A-PLDW100-12/4	12.0	4.0	1.78	2.5
HTB-A-PLDW100-18/6	18.0	6.0	2.25	2.0
HTB-A-PLDW100-24/8	24.0	8.0	2.54	2.0

4:1 Ratio Mini Boxes

Ordering Description	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Maximum ID Recovered (mm)	Mini Box Quantity (m)
HTB-A-PLDW100-4/1	4.0	1.0	1.00	3.5
HTB-A-PLDW100-8/2	8.0	2.0	1.00	3.5
HTB-A-PLDW100-12/3	12.0	3.0	1.40	3.0
HTB-A-PLDW100-16/4	16.0	4.0	1.78	2.0
HTB-A-PLDW100-24/6	24.0	6.0	2.25	2.0

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.