

## PLDW100

High shrink ratio, adhesive lined, moisture resistant polyolefin

PLDW100 is a 3:1 shrink ratio, general purpose, flexible, polyolefin tubing with a thermoplastic adhesive inner liner. The inner liner will melt and flow to environmentally seal and protect components and interconnections.

### FEATURES & BENEFITS

- 3:1 shrink ratio allows for connector-to-cable sealing.
- Medium wall provides increased mechanical protection.
- Adhesive bonds to a wide variety of plastics, rubbers and metals including polyethylene, aluminium, steel and copper.

### APPLICATIONS

- Environmentally seals and protects a wide variety of electrical applications.
- High expansion ratio for cable jacket repair without removing connectors.
- Strain relief and mechanical protection.

General Information	
Material Jacket	Polyolefin
Inner Liner	Polyamide
Shrink Ratio	3:1
Operating temperature	-55°C to 110°C
Dielectric Strength	12 KV/mm
Installation Temperature	80°C to 110°C
Specifications	UL E85381 RoHS AMS DTL 23053/4



### Standard Colours

<b>Black</b>	<b>Clear</b>
--------------	--------------

Ordering Description	Ordering Size (inches)	Minimum ID Supplied (mm)	Maximum ID Supplied (mm)
PLDW100-3/1	3.0	1.0	1.00
PLDW100-4.5/1.5	4.5	1.5	1.10
PLDW100-6/2	6.0	2.0	1.10
PLDW100-9/3	9.0	3.0	1.40
PLDW100-12/4	12.0	4.0	1.78
PLDW100-18/6	19.0	6.0	2.25
PLDW100-24/8	24.0	8.0	2.54
PLDW100-39/13	40.0	13.0	2.54

PACKAGING OPTIONS - SPOOLS, COILS, MINI BOXES, 1.2M LENGTHS AND BESPOKE CUT PIECES

Full details on technical specifications, test methods and values are available on request.

