

## PLT100 (A)

MEDIUM WALL HEAT SHRINKABLE POLYOLEFIN WITH OPTIONAL ADHESIVE LINER

PLT100 (A) is a heavy wall tubing which is suitable for a wide range of telecom and low voltage power applications such as jointing and cable repair. PLT100 (A) tubing combines a good level of electrical and physical protection. It is available with or without an adhesive liner.



### TECHNICAL DATA

#### MEDIUM WALL HEAT SHRINKABLE POLYOLEFIN

Material	Polyolefin
Inner Liner	Polyamide
Shrink Ratio	>3:1
Dielectric Strength	≥ 20 KV/mm
Installation Temperature	120 °C
Specifications	RoHS Compliant

### BENEFITS

- Rugged and hard wearing.
- Continuous operating temperature of -55 °C to +110 °C.
- Adhesive lining provides a watertight seal.
- Offer strain relief and mechanical protection.
- Excellent chemical and abrasion resistance.

Ordering Description	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Recovered Wall Thickness (mm)
PLT100(A)-9/3	9.0	3.0	2.50
PLT100(A)-12/4	12.0	4.0	2.50
PLT100(A)-16/5	16.0	5.0	2.60
PLT100(A)-20/6	20.0	6.0	2.80
PLT100(A)-30/8	30.0	8.0	3.20
PLT100(A)-45/12	45.0	12.0	4.00
PLT100(A)-55/16	55.0	16.0	4.10
PLT100(A)-65/19	65.0	19.0	4.20
PLT100(A)-80/22	80.0	22.0	4.20
PLT100(A)-100/30	100.0	30.0	4.40
PLT100(A)-120/34	120.0	34.0	4.40
PLT100(A)-140/37	140.0	37.0	4.50
PLT100(A)-160/50	160.0	50.0	4.50
PLT100(A)-180/60	180.0	60.0	4.50

## QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.