

PMGCOMPANY

SPECIALISTS IN HEAT SHRINK TUBING AND CABLE HARNESSING PRODUCTS



RT375

TRANSPARENT FLAME RETARDANT HEAT SHRINKABLE TUBING

RT375 is 2:1 shrink ratio, thin wall, transparent, flame retardant, heat shrinkable tubing. RT375 has been developed primarily for the protection, bundling and jacketing of wires and cables whilst permitting their identification or inspection. It is capable of withstanding extreme abuse, affords UV protection and operates at a high temperature.



TECHNICAL DATA

TRANSPARENT FLAME RETARDANT HEAT SHRINKABLE TUBING

Material	Polyolefin
Shrink Ratio	2:1
Operating Temperature	-55 °C to 150 °C
Dielectric Strength	15 KV/mm
Installation Temperature	150 °C
Specifications	UL 224 VW-1 RoHS AMS-DTL 23053/18 Class 2

APPLICATIONS

- Electrical insulation of wires and cables.
- Protection against abrasion and UV.
- Protection of identification labels, transparency allows for easy inspection.

BENEFITS

- Transparent and flame retardant to UL224 VW-1.
- Offers protection from UV degradation.
- Operates at high temperatures.
- Offers excellent mechanical protection.

Ordering Description	Ordering Size (Inches)	Minimum ID Supplied (mm)	Maximum ID Supplied (mm)	Recovered Wall Thickness (mm)
RT375-3/64	3/64	1.20	0.60	0.45
RT375-1/16	1/16	1.60	0.80	0.45
RT375-3/32	3/32	2.40	1.20	0.50
RT375-1/8	1/8	3.20	1.60	0.50
RT375-3/16	3/16	4.80	2.40	0.50
RT375-1/4	1/4	6.40	3.20	0.65
RT375-3/8	3/8	9.50	4.80	0.65
RT375-1/2	1/2	12.70	6.40	0.65
RT375-3/4	3/4	19.00	9.50	0.75
RT375-1	1	25.40	12.70	0.90

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.