



HD-LUGS

HEAVY DUTY TERMINAL LUGS

These heavy duty terminal lugs are manufactured from highly conductive electrolytic copper with a bright tin finish. HD Lugs offer outstanding resistance to oxidation and corrosion and are perfect for where easy, quick and reliable installation is required.

APPLICATIONS & BENEFITS

- Ideal for panel building, telecoms and utilities applications.
- Designed primarily for compression crimping.
- Can be used with a wide variety of European stranded and flexible cables.
- Suited to connect copper conductors to equipment terminals.
- Bell mouth entry for easy cable insertion.
- Inspection holes as standard to check cable is properly inserted before crimping.
- RoHS compliant.



Cable Size mm ²	Stud Size mm	Dimensions (mm)							
		A	B	W	E	F	D	L	T
10	5.6	6.9	4.4	11.0	5.9	5.1	9.0	27.0	2.0
	8.0	6.9	4.4	14.0	9.7	8.3	10.0	35.0	1.6
	10,B	6.9	4.4	16.0	12.0	10.0	10.0	39.0	1.5
	12.0	6.9	4.4	18.0	12.0	10.0	10.0	39.0	2.0
16	5.6	8.0	5.6	11.5	5.9	5.1	11.0	28.5	2.2
	8.0	8.0	5.6	14.0	9.7	8.3	13.0	38.0	1.8
	10,B	8.0	5.6	16.0	12.0	10.0	13.0	42.0	1.6
	12.0	8.0	5.6	18.0	12.0	10.0	13.0	42.0	1.3
25	5,6,8	9.5	7.0	13.5	5.9	8.3	13.0	40.0	2.4
	10,B	9.5	7.0	16.0	9.7	10.0	13.0	44.0	2.0
	12.0	9.5	7.0	18.0	12.0	10.0	13.0	44.0	1.8
35	5,6,8	11.0	8.2	15.5	9.7	8.3	14.0	41.0	2.8
	10,B	11.0	8.2	15.5	12.0	10.0	14.0	45.0	2.8
	12.0	11.0	8.2	18.0	12.0	10.0	14.0	45.0	2.5
50	5,6,8	12.1	9.5	17.2	9.7	8.3	18.0	46.0	2.6
	10,12,B	12.1	9.5	17.2	12.0	10.0	18.0	50.0	2.6
70	5,6,8	15.0	11.5	21.4	9.7	8.3	18.0	48.0	3.5
	10,12,B	15.0	11.5	21.4	12.0	10.0	18.0	25.0	3.5
	14,16	15.0	11.5	21.4	16.5	16.5	18.0	64.0	3.5

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.