


SPECIALISTS IN HEAT SHRINK TUBING AND CABLE HARNESSING PRODUCTS



PL-CON-ZH

ZERO HALOGEN PRINTABLE HEAT SHRINK SLEEVING

The PL-CON-ZH heat shrinkable marking sleeve is manufactured from a halogen free, flame retardant and low smoke heat shrinkable polyolefin tubing. The product has been designed specifically with printability in mind and as such has all the properties required to make this an ideal product for identification purposes.



The compound of the tubing is free of halogens and offers excellent low fire hazard characteristics combined with minimal smoke emission.

TECHNICAL DATA

ZERO HALOGEN PRINTABLE HEAT SHRINK SLEEVING

Material	Cross Linked Polyolefin
Shrink Ratio	2:1
Operating Temperature	-30 °C to 105°C
Specifictions	Adherence: (SAE-AS5942/MIL81531-1998 Clause 3.4.2/4.6.2) Resistance to solvents:-MIL-STD-202G Test Method 215 (2002) (MIL81531/SAEA81531-1998 Clause 3.4.3)
Recommended Printer	CAB A4+ 300 dpi Printer
Recommended Ribbon	FTI-Y, FTI-X

APPLICATIONS

Common uses include cable identification and marking as well as insulation, wire bundling and mechanical protection.

Ordering Description	Minimum Supplied ID (Inches)	Minimum Supplied ID (mm)	Maximum Recovered ID (mm)	Spool (m)
PL-CON-ZH-2.4	3/32	2.4	1.2	50
PL-CON-ZH-3.2	1/8	3.2	1.6	100
PL-CON-ZH-4.8	3/16	4.8	2.4	100
PL-CON-ZH-6.4	1/4	6.4	3.2	100
PL-CON-ZH-9.5	3/8	9.5	4.8	100
PL-CON-ZH-12.7	1/2	12.7	6.4	100
PL-CON-ZH-19.0	3/4	19.0	9.5	TBA
PL-CON-ZH-25.4	1	25.4	12.7	100
PL-CON-ZH-38.1	1-1/2	38.1	19.1	60
PL-CON-ZH-50.8	2	50.8	25.4	TBA

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.

