

# PMGCOMPANY

SPECIALISTS IN HEAT SHRINK TUBING AND CABLE HARNESSING PRODUCTS



## VERSAFLEX-FR

POLYESTER FLAME RETARDANT EXPANDABLE BRAIDED SLEEVING

Versaflex-FR is an expandable braided sleeve constructed from a flame retardant PET material. The 0.25mm monofilament yarns include flame retardant additives to achieve the self-extinguishing rating of UL VW1. The special braided characteristics allows for the expansion of its internal diameter, whilst contracting it's length, Versaflex-FR braid is very flexible and resistant to most chemicals and solvents.



### TECHNICAL DATA

#### POLYESTER FLAME RETARDANT EXPANDABLE BRAIDED SLEEVING

Material	Polyester (PET)
Monofilament Size	0.22mm or 0.26mm
Operating Temperature	-60 °C to 160 °C
Operating Temperature Short Periods	220 °C
Cutting Tool	Hot Knife
Specifications	RoHS

### APPLICATIONS

- Automotive wire and hose protection.
- Abrasion protection in commercial applications.
- Protection of air conditioning hoses.

## BENEFITS

- Highly expandable to allow for easy installation.
- Flame retardant with conformance to UL VW-1.
- Zero halogen and low fire hazard.

Nominal Size (Inches)	Min (mm)	Cable Usage	Max (mm)	Spool Size (m)
1/8	2.4		6.4	200
3/16	3.0		9.0	200
1/4	3.2		9.5	200
3/8	5.7		16.0	100
1/2	6.4		19.0	100
3/4	13.0		32.0	100
1	18.0		34.0	50
1-1/4	19.0		45.0	50
1-1/2	25.0		60.0	50
1-3/4	32.0		70.0	25
2	38.0		76.0	25

## QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.