

HTB-A

Adhesive Lined Heat Shrink Tubing Mini-Spool Boxes

HTB-A's are mini spool boxes containing either 3:1 or 4:1 adhesive lined heat shrinkable tubing. The tubing contained within the boxes is a general purpose, flexible polyolefin tubing with a thermoplastic adhesive liner. The inner liner will melt and flow to environmentally seal and protect components and interconnections.

Features & Benefits

- 3:1 and 4:1 ratio allows for connector-to-cable sealing.
- Medium wall provides increased mechanical protection.
- Adhesive bonds to a wide variety of plastics, rubbers and metals including polyethylene, aluminum, steel and copper.

Applications

- Protection against abrasion and chemicals
- Wire bundling and splice protection
- Cable identification and strain relief
- Sealing and waterproofing of cables



General Information	
Shrink Ratio	3:1 or 4:1
Operating temperature	-55°C to 110°C
Installation Temperature	110°C
Specifications	CSA RoHS AMS DTL 23053/4

Available Colours

BLACK	CLEAR
-------	-------

3:1 ratio mini boxes

Ordering Description	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Recovered Wall Thickness (mm)	Mini Box Quantity (m)
HTB-A-PLDW100-3/1	3.0	1.0	1.00	5
HTB-A-PLDW100-6/2	6.0	2.0	1.10	4
HTB-A-PLDW100-9/3	9.0	3.0	1.40	3
HTB-A-PLDW100-12/4	12.0	4.0	1.78	2.5
HTB-A-PLDW100-18/6	18.0	6.0	2.25	2
HTB-A-PLDW100-24/8	24.0	8.0	2.54	2

4:1 ratio mini boxes

Ordering Description	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Recovered Wall Thickness (mm)	Mini Box Quantity (m)
HTB-A-PLDW104-4/1	4.0	1.0	1.00	3.5
HTB-A-PLDW104-8/2	8.0	2.0	1.00	3.5
HTB-A-PLDW104-12/3	12.0	3.0	1.40	3
HTB-A-PLDW104-16/4	16.0	4.0	1.78	2
HTB-A-PLDW100-24/6	24.0	6.0	2.25	2

Full details on technical specifications, test methods and values are available on request.

