



PPS-OSW

OPEN STRUCTURE SELF-CLOSING WRAP

PPS-OSW self-closing open structure polyester wrap offers an innovative solution for breakout protection and allows for easy removal during cable repair or maintenance. The open structure also allows for other components to be installed, for example copper terminals and connectors. Another key feature is exceptional abrasion resistance and flame retardance, this product is also zero halogen.



TECHNICAL DATA

OPEN STRUCTURE SELF-CLOSING WRAP

Material	Polyester
Flammability	UL94-V2
Operating Temperature	-50 °C to +150 °C
Melt Point	240°C ±10°C
Standard Colour	Black
Certified	RoHS

APPLICATIONS

- PPS-OSW can be used on a variety of wire harness applications including automotive and rail, where wire and cables need durable abrasion resistant protection.

Ordering Description	Internal Diameter (mm)	Overlap (%)	Maximum Bundle Diameter (mm)
PPS-OSW-006	6	25	7
PPS-OSW-009	9	25	10
PPS-OSW-013	13	25	14
PPS-OSW-016	16	25	17
PPS-OSW-019	19	25	20
PPS-OSW-025	25	25	26
PPS-OSW-032	32	25	33
PPS-OSW-038	38	25	40
PPS-OSW-050	50	25	52

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.