

PPS-OSW

Open Structure Self-Closing Wrap



PPS-OSW self-closing open structure polyester wrap offers an innovative solution for breakout protection and allows for easy removal during cable repair or maintenance. The open structure also allows for other components to be installed, for example copper terminals and connectors. Another key feature is exceptional abrasion resistance and flame retardance, this product is also zero-halogen

Applications

PPS-OSW can be used on a variety of wire harness applications including automotive and rail, where wire & cables need durable abrasion resistant protection.

Technical data	
Material	Polyester
Operating temperature	-50°C to +150°C
Flammability	UL94-V2
Certified	RoHS
Standard colour	Black
Melt Point	240°C ± 10°C

Ordering Description	Internal Diameter (mm)	Overlap (%)	Max Bundle Diameter (mm)
PPS-OSW-006	6	25%	7
PPS-OSW-009	9	25%	10
PPS-OSW-013	13	25%	14
PPS-OSW-016	16	25%	17
PPS-OSW-019	19	25%	20
PPS-OSW-025	25	25%	26
PPS-OSW-032	32	25%	33
PPS-OSW-038	38	25%	40
PPS-OSW-050	50	25%	52

Packaging options

Special sizes & colours available on request.
Cutting Tool: Hot Knife/ Scissors.

Full details on technical specifications, test methods and values are available on request.

