

# PMGCOMPANY

SPECIALISTS IN HEAT SHRINK TUBING AND CABLE HARNESSING PRODUCTS



## PPS-VBW

### VELCRO BRAIDED WRAP

PPS-VBW is a polyester braided wrap with a polyamide velcro fixing method. This product can also be easily re-opened when cables need to be managed or removed. Cable breakouts can be made simply by bringing the cables out through the velcro fixing.



## TECHNICAL DATA

### VELCRO BRAIDED WRAP

Material	Polyester (PET)
Velcro Material	Polyamide
Operating Temperature	-50 °C to + 150 °C
Flammability	UL VW-1
Melt Point	240+/- 10 °C
Cutting Method	Hot Knife
Specifications	UL VW-1 RoHS

## APPLICATIONS

- Widely used in management of A/V cables.
- To tidy cables and power cords in the office and home environments.

## BENEFITS

- Creates a tidy well regulated environment.
- Easy to install.
- Easy to re-open.
- Easy to create cable breakouts.

Ordering Description Metric	Nominal Size (mm)	Velcro Width (mm)	Max Bundle Diameter (mm)
PPS-VBW-013	13.0	10.0	8.0
PPS-VBW-019	19.0	10.0	12.0
PPS-VBW-032	32.0	20.0	20.0
PPS-VBW-051	51.0	20.0	32.0
PPS-VBW-064	64.0	20.0	40.0

## QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.