

PMGCOMPANY

SPECIALISTS IN HEAT SHRINK TUBING AND CABLE HARNESSING PRODUCTS



PPS-WRAP

POLYESTER WRAP-AROUND BRAIDED SLEEVING

PPS-WRAP is a flexible wrap-around protective sleeve. The woven construction provides flexibility, spring back and high resistance to abrasion. It is designed to protect wiring, cables, pipes, and hoses from mechanical degradation arising from exposure to challenging conditions in vibrating installations. PPS-WRAP is installed by opening the sleeve, feeding over the application and releasing.



TECHNICAL DATA

POLYESTER WRAP-AROUND BRAIDED SLEEVING

Material	Polyester (PET)
Monofilament Size	0.22mm or 0.25mm
Operating Temperature	-50 °C to 150 °C
Melt Point	240°C ±10°C
Cutting Tool	Hot Knife
Specifications	RoHS Halogen Free

APPLICATIONS

- Mechanical protection of wires in motor vehicles and trains.
- Used to minimize vibration of hoses and wire harnesses.
- Industrial applications where abrasion resistance and cut through protection is key.

BENEFITS

- Side entry (post termination) application.
- Ideal for the repair and re-routing of cables.
- Light weight and cost effective.
- Zero halogen and low fire hazard.

Ordering Description	Nominal Internal Diameter (mm)	Maximum Bundle Diameter (mm)
PPS-WRAP-5	5.0	6.0
PPS-WRAP-9	9.0	10.0
PPS-WRAP-10	10.0	11.0
PPS-WRAP-13	13.0	14.0
PPS-WRAP-19	19.0	20.0
PPS-WRAP-25	25.0	27.0
PPS-WRAP-30	30.0	32.0
PPS-WRAP-50	50.0	52.0

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.