



RPR

ADHESIVE LINED HEAT SHRINKABLE WRAP-AROUND SLEEVING

RPR wrap-around sleeve incorporates a stainless-steel channel which is simply slid into position and keeps the wrap-around tubing in place during installation. The wrap-around sleeves are made from thermally stabilised, polymeric halogen free material. The outer surface of the sleeves have thermochromic paint.



TECHNICAL DATA

ADHESIVE LINED HEAT SHRINKABLE WRAP-AROUND SLEEVING

Material	Polymeric
Flammability	Halogen Free
Tensile Strength	17.5 N/mm ² (Min)
Dielectric Strength	12 KV/mm (Min)
Ultimate Elongation	300% (Min)
Water Absorption	0.1% (Max)
Thermal Aging (120°C for 500 hours)	Tensile Strength 15 N/mm ² Ultimate Elongation 200% (Min)

APPLICATIONS

- Corrosion protection for cables that are exposed to pollutants.
- Can be used in a wide range of cable diameters.
- Repair and protection of cables.

BENEFITS

- Watertight insulation, good chemical resistance.
- Quick and easy to install.
- Cable range 12mm to 150mm.
- Can be easily cut to length required.

Size (mm)	Application Range (mm)	Minimum ID Supplied (mm)	Maximum ID Recovered (mm)	Layflat Diemension Supplied (mm)	Length (m)
43/8	12.0-25.0	43.0	8.0	145.0 ± 5.0	1.0
52/10	15.0-35.0	52.0	10.0	175.0 ± 5.0	1.0
82/22	20.0-50.0	82.0	22.0	260.0 ± 10.0	1.0
100/30	30.0-70.0	100.0	30.0	350.0 ± 10.0	1.0
139/38	40.0-90.0	139.0	38.0	460.0 ± 10.0	1.0
185/55	60.0-120.0	185.0	55.0	576.0 ± 10.0	1.0

QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.