

# PMGCOMPANY

SPECIALISTS IN HEAT SHRINK TUBING AND CABLE HARNESSING PRODUCTS



## VERSAFLEX

### POLYESTER EXPANDABLE BRAIDED SLEEVING

Versaflex sleeving is suited for the mechanical protection of wire harnesses, hoses, and all other applications where exceptional flexibility combined with superior abrasion/cut resistance is required.



## TECHNICAL DATA

### POLYESTER EXPANDABLE BRAIDED SLEEVING

Material	Polyester (PET)
Monofilament Size	0.22mm or 0.26mm
Operating Temperature	-60 °C to 160 °C
Operating Temperature Short Periods	220 °C
Cutting Tool	Hot Knife
Specifications	RoHS

Versaflex serves as an economical means for wire bundling that will trap heat or moisture; expanding easily to fit over irregular shapes then contracting to conform and grip. Hot knife is recommended for cutting to prevent fraying.

## BENEFITS

- Highly expandable to allow for easy installation.
- Excellent abrasion and cut-through resistance, fungus proof.
- Not affected by most chemicals and solvents.
- Zero halogen and low fire hazard.

Ordering Description Metric	Nominal Size (mm)	Cable Bundle Usage Range (Diameter)	
		Minimum (mm)	Maximum (mm)
Versaflex-3	3.0	1.0	6.0
Versaflex-4	4.0	2.0	7.0
Versaflex-5	5.0	2.5	8.0
Versaflex-6	7.0	3.0	9.0
Versaflex-8	8.0	5.0	16.0
Versaflex-10	10.0	7.0	19.0
Versaflex-12	12.0	8.0	24.0
Versaflex-15	15.0	10.0	27.0
Versaflex-20	20.0	14.0	30.0
Versaflex-25	25.0	18.0	35.0
Versaflex-30	30.0	20.0	50.0
Versaflex-40	40.0	30.0	60.0
Versaflex-50	50.0	40.0	80.0

## QUALITY ASSURANCE

PMG Company promises to always strive to offer our customers quality assurance. We aim to provide consistent and exceptional levels of customer service. This is achieved by our experienced sales and logistics teams. Quality assurance is our way of preventing mistakes and avoiding problems when delivering products to our customers. The high quality products we supply also conform to internationally recognised product specifications and standards.